
SERIES 375 RAILING INSTALLATION INSTRUCTIONS

REVISION 0.0 (4/16/2020)




PLEASE READ THESE INSTRUCTIONS IN THEIR ENTIRETY PRIOR TO ASSEMBLING RAILING. IF YOU HAVE ANY QUESTIONS OR NEED ASSISTANCE, PLEASE CALL ONE OF THE NUMBERS BELOW.


DRAWING TITLE:

OVERVIEW, RAILING

DATE: 4/16/2020 DRAWN BY: TJC







RECOMMENDED TOOLS

- SCISSORS
- CENTER PUNCH
- DRILL
- Ø11/64" DRILL BIT
- MASKING TAPE
- SOAP
- #2 PHILLIPS SCREW DRIVER BIT
- IMPACT DRIVER
- LEVEL
- PENCIL
- TAPE MEASURE
- STRING LINE
- SHIMS
- SPEED SQUARE
- ELECTRIC MITER SAW WITH A 10" CARBIDE BLADE SPECIFICALLY FOR CUTTING ALUMINUM
- RUBBER MALLET
- 4" C-CLAMP


DRAWING TITLE:

OVERVIEW, PARTS LIST

(2) PICKET VINYL INSERT @ 6'-6"

DATE: 4/16/2020 DRAWN BY: TJC





SAMPLE DECK PLAN

NOT TO SCALE

THINGS TO NOTE:

- WHICH SIDES OF YOUR POSTS GET DRILLED FOR RAILING CONNECTION BLOCKS.
- MAXIMUM POST SPACING IS 6'-0" FROM CENTER OF POST TO CENTER OF POST.
- ALL GAPS, INCLUDING THE SPACE BETWEEN A WALL AND A POST CANNOT EXCEED 4".
- THE CENTERLINE OF YOUR RAILING SHOULD BE A MINIMUM OF 4" FROM THE EDGE OF DECK.
- IT IS RECOMMENDED THAT YOU SHOULD SPACE YOUR POSTS AN EQUAL DISTANCE APART WHEREVER POSSIBLE.


DRAWING TITLE:

OVERVIEW, SAMPLE DECK PLAN

DATE: 4/16/2020 DRAWN BY: TJC








OVERVIEW, DIMENSIONS

DATE: 4/16/2020 DRAWN BY: TJC







STEP 1: RCB INSTALLATION

DATE: 4/16/2020 DRAWN BY: TJC










CENTER PUNCH AND DRILL BOTTOM HOLES

INSTALL BOTTOM CONNECTING BLOCK



RAIL CONNECTING BLOCK (RCB) **USE PHILLIPS BIT** AND DRILL TO INSTALL (2X) #10 X 2" SCREWS POST

CENTER PUNCH AND DRILL TOP HOLES


INSTALL TOP CONNECTING BLOCK

DRAWING TITLE:

STEP 1: RCB INSTALLATION

DATE: 4/16/2020 DRAWN BY: TJC






STEP 2: BASE PLATE INSTALLATION

DATE: 4/16/2020

DRAWN BY: TJC





THINGS TO NOTE:


- USING A TAPE MEASURE AND A STRING LINE, PLACE ALL OF YOUR POSTS IN THEIR PROPER LOCATIONS PER YOUR DECK PLANS.
- USE A LEVEL ON TWO ADJACENT SIDES OF EACH POST TO ENSURE THE POST IS PLUMB. IF IT IS NOT, USE SHIMS AS REQUIRED UNDER THE BASE PLATE.
- BE SURE TO FOLLOW MINIMUM AND MAXIMUM DIMENSIONAL REQUIREMENTS AS LISTED ON THE SAMPLE DECK PLAN.

DRAWING TITLE:

STEP 3: PLACING THE POSTS

DATE: 4/16/2020 DRAWN BY: TJC





SAMPLE ONLY

LAG BOLTS NOT INCLUDED


DRAWING TITLE:

STEP 3: TYP WOOD CONNECTION

DATE: 4/16/2020

DRAWN BY: TJC





SAMPLE ONLY


ANCHOR BOLTS NOT INCLUDED

DRAWING TITLE:

STEP 3: TYP CONCRETE CONNECTION

DATE: 4/16/2020 DRAWN BY: TJC





THINGS TO NOTE:


- INSTALL ALL POSTS BEFORE CUTTING TOP AND BOTTOM RAILS.
- USE AN ELECTRIC MITER SAW WITH A 10" CARBIDE BLADE SPECIFICALLY FOR CUTTING ALUMINUM.
- CUT AND DOUBLE CHECK FIT BEFORE ATTACHING RAILS WITH SCREWS


DRAWING TITLE:

STEP 4: TOP AND BOTTOM RAIL

DATE: 4/16/2020 DRAWN BY: TJC








INSTALL BOTTOM RAIL BEFORE TOP RAIL

DRAWING TITLE:

STEP 4: BOTTOM RAIL INSTALLATION

DATE: 4/16/2020 DRAWN BY: TJC





INSTALL BOTTOM RAIL BEFORE TOP RAIL

DRAWING TITLE:

STEP 4: TOP RAIL INSTALLATION

DATE: 4/16/2020 DRAWN BY: TJC



PICKET SPACER CUT LENGTH CALCULATOR

THE PICKET SPACERS COME PRE CUT TO 3.875" (3-7/8"). HOWEVER, TO CENTER YOUR PICKETS BETWEEN THE POSTS, YOU WILL NEED TO CUT THE 4 END SPACERS (SEE ARROWS BELOW) IN EACH RAILING RUN.

THIS IS THE CALCULATION TO DETERMINE THAT CUT LENGTH.

(A) = INSIDE DISTANCE EXAMPLE: 69.25

(B) = (A) DIVIDED BY 4.5 EXAMPLE: 69.25 / 4.5 = 15.39

(C) = ROUND (B) DOWN TO WHOLE EXAMPLE: IF (B) = 15.39, THEN (C) = 15

(D) = (C) - 1 EXAMPLE: 15 - 1 = 14


 $(E) = (C) \times 0.625$ EXAMPLE: 15 × 0.625 = 9.375

 $(F) = (D) \times 3.875$ EXAMPLE: 14 × 3.875 = 54.250

(G) = (A) - (E) - (F) EXAMPLE: 69.25 - 9.375 - 54.25 = 5.625

(H) = (G) / 2 EXAMPLE: 5.625 / 2 = 2.8125

CUT 4 SPACERS EQUAL TO (H)




DRAWING TITLE:


STEP 5: PICKET INFILL


DATE: 4/16/2020 DRAWN BY: TJC






INSTALL VINYL EXTRUSION





CUT AND INSTALL FIRST PICKET SPACER




* USE A C-CLAMP OR RUBBER MALLET TO ASSIST SNAPPING THE SPACERS ONTO THE RAIL IF NEEDED

DRAWING TITLE:


STEP 5: PICKET INFILL


DATE: 4/16/2020 DRAWN BY: TJC






INSTALL PICKET AND NEXT SPACER






REPEAT PICKETS AND SPACERS




* USE A C-CLAMP OR RUBBER MALLET TO ASSIST SNAPPING THE SPACERS ONTO THE RAIL IF NEEDED

STEP 5: PICKET INFILL

DATE: 4/16/2020 DRAWN BY: TJC






STEP 5: PICKET INFILL

DATE: 4/16/2020 DRAWN BY: TJC





STEP 6: TOP CAP INSTALLATION

DATE: 4/16/2020 DRAWN BY: TJC

